



## VOLKAN 1200

### How it works

The VOLKAN 1200 is a top-loading incinerator with a unique design. The operator simply glides back the two independent doors, which form the lid to gain access to the hearth. Waste can then be easily loaded into the incinerator. Once loaded, the appropriate burn program is selected, allowing operators to leave the incinerator unattended while the waste is reduced to ash. The highly efficient design of this incinerator quickly heats the after chamber to the required temperature, automatically starting the main burner to begin combustion in the main chamber. Automatic systems continue to monitor both temperature and time throughout the selected program, safely ending the cycle with an appropriate cool-down period.

Automatic systems ensure that the after chamber gasses quickly reach 850°C, and maintains this as a minimum until the end of the main burn cycle, meeting the EU Animal By-Products Regulation requirement that all exhaust gasses are subjected to a minimum of 850°C for a minimum of 2 seconds. This incinerator can also deliver significant fuel savings as it constantly monitors the temperature throughout each cycle, automatically turning burners off as the temperature rises, and on again when required.

The incinerator must be installed on a concrete hard standing with suitable 230-volt electricity and fuel supplies provided, and sufficient clearance for the height of the chimney assembly. Final assembly is



### Specifications

Chamber Volume	2.38m <sup>3</sup>	2.2m(l) x 0.9m(w) x 1.2m(h)
Load Capacity	900-1200 kg	
Load Method	Top	
Fuel Options	Diesel, Natural Gas, LPG, Bio-fuel	
Electricity Supply	230 volt required	
Weight	3.9 tonnes	
Dimensions	3.3m(l) x 2.9m(w) x 2.1m(h)	
Time to temperature	From 25 minutes	
Fuel Consumption*	Liquid Propane Gas: 6 to 8 litres per hour Natural Gas: 7 to 9 Nm <sup>3</sup> /hr Diesel: 8 to 10 litres per hour	

\*Figures based on typical figures gained from an average burn cycle.  
Waste Spectrum Environmental Ltd continually strives to improve its products and therefore reserves the right to introduce modifications to their product range without notice.

carried out by a fully trained Waste Spectrum engineer, who will commission the incinerator and train your operators in its correct and safe operation. A comprehensive operating, care & maintenance manual is provided with each incinerator.

# www.wastespectrum.com

**For more information contact:**  
email: [sales@wastespectrum.com](mailto:sales@wastespectrum.com)  
telephone: +44(0)1905 362100  
fax: +44(0)1905 362101

**Or visit us at:**  
[www.wastespectrum.com](http://www.wastespectrum.com)